

U.L. Listed Tapes

UL 181A-P/B-FX Listed aluminum foil HVAC tape for joining and sealing joints. A tape that "does it all," AF 100 is engineered to form airtight bonds on joints and seams in application temperatures ranging from -20 F to 260 F and in humid conditions.

- Printed aluminum foil tape
- Excellent adhesion to rigid fiberglass duct board and flexible air duct
- Flexible and easy to use to create airtight bonds
- Superior stability during extreme fluctuations in temperature
- Applicable Standards: Tested in accordance with UL 723; FSI 25/SDI 50; UL 181A-P/B-FX Listed; US Green Building Council – LEED® Point contributor product



| MARS NO. | DESCRIPTION | SIZE | MARS PACK |
|----------|--------------------|------------------|-----------|
| 79087 | U.L. 181 foil tape | 2 1/2" x 60 yds. | 16 |

Spray Adhesive

MARS #79094 is especially designed to bond polyethylene to itself, concrete block, wood and other hard to bind surfaces. Does not contain methylene chloride. Very quick, aggressive tack. Excellent for HVAC insulation applications.



| MARS NO. | DESCRIPTION | MARS PACK |
|----------|----------------------------|-----------|
| 79094 | Spray adhesive, 17 fl. oz. | 12 |

Liquid Electrical Tape

- Forms an airtight, protective, waterproof, UV resistant, dielectric coating
- Will not peel or unravel
- Patented, UL-tested, fast drying formula



| MARS NO. | DESCRIPTION | MARS PACK |
|----------|--------------------------------------|-----------|
| 86135 | Liquid electrical tape (black), 4oz. | 1 |

PVC Electrical Tape

PVC electrical tape provides excellent adhesion to aluminum and copper conductors and plastic and rubber insulations where quick identification is most needed. Due to its primary use in low temperatures, it can be stretched to conform to any shape without breaking. UL listed and CSA approved. PVC electrical tape is designed for general splicing and as a protective outer jacket. Flame retardant and cold and weather resistant. UL listed and CSA approved.



| MARS NO. | DESCRIPTION | MARS PACK | CASE QTY. |
|----------|--------------------|-----------|-----------|
| 86186 | 3/4" x 66' - red | 1 | 100 |
| 86187 | 3/4" x 66' - white | 1 | 100 |
| 86188 | 3/4" x 66' - green | 1 | 100 |
| 86189 | 3/4" x 66' - blue | 1 | 100 |
| 86184 | 3/4" x 66' - black | 1 | 100 |
| 86133* | 3/4" x 60' - black | 10 | 100 |

* Non-UL

Low Density Thread Seal Tape



- Thickness 3 mills.
- Standard grade, low density
- Provides a highly resistant seal on pipe threads for all types of service
- Suitable for use with solvents, chemicals, oxygen, and on food lines
- Non-toxic
- Permits easy disassembly, even after years of service
- Meets Mil. Spec. T-27730A
- Sealing temperature range: -450°F to 550°F (-268°C to 288°C)
- Working pressures: 2,000 PSI (136 BAR)
- Sold in case quantities only



| MARS NO. | DESCRIPTION | CASE QTY. |
|----------|-------------|-----------|
| 95409 | 1/2" x 260" | 144 |
| 95410 | 1/2" x 520" | 144 |
| 95412 | 3/4" x 520" | 144 |