

CONSTANT TORQUE AIR HANDLERS

AMC FEATURES

- Available for cooling and heat pump applications
- Multi-speed ECM blower motor
- Factory-sealed cabinet certified to achieve 2% or less leakage rate at 1.0 inch water column
- Multi-position installation
- Horizontal and vertical condensate drain pans standard
- Blower and coil slide out for ease of maintenance
- Field installed heater kits are optional: 5/7.5/10/15/20kW
- AHRI Listed & ETL Certified



AMC SPECS AT A GLANCE

| Model | Voltage | Hertz | HP | Speeds | Circuit Amps | Max Circuit Protector | Dimensions (in.) (H x W x D) |
|----------|---------|-------|-----|--------|--------------|-----------------------|---------------------------------|
| AMC24S1A | 208/230 | 60 | 1/3 | 5 | 2.6 | 15(A) | 41-3/8 x 18-1/8 x 20-1/2 |
| AMC36S1A | 208/230 | 60 | 1/2 | 5 | 3.0 | 15(A) | 46-1/2 x 19-5/8 x 21-5/8 |
| AMC60S1A | 208/230 | 60 | 3/4 | 5 | 4.5 | 15(A) | 54-1/2 x 22 x 24 |



**Come Home to Comfort.
Come Home to *Comfort-Aire*.**

PSC AIR HANDLERS

AMP FEATURES

- Available for cooling and heat pump applications
- All aluminum tubes & fins
- Factory-sealed cabinet certified to achieve 2% or less leakage rate at 1.0 inch water column
- Multi-position installation
- Horizontal and vertical condensate drain pans standard
- Blower and coil slide out for ease of maintenance
- Field installed heater kits are optional: 5/7.5/10/15/20kW
- AHRI Listed & ETL Certified



AMP SPECS AT A GLANCE

| Model | Voltage | Hertz | HP | Speeds | Circuit Amps | Max Circuit Protector | Dimensions (in.) (H x W x D) |
|----------|---------|-------|-----|--------|--------------|-----------------------|---------------------------------|
| AMP24S1A | 208/230 | 60 | 1/5 | 3 | 2.6 | 15(A) | 46-1/2 x 19-5/8 x 21-5/8 |
| AMP36S1A | 208/230 | 60 | 1/3 | 3 | 3.2 | 15(A) | 46-1/2 x 19-5/8 x 21-5/8 |
| AMP48S1A | 208/230 | 60 | 1/2 | 3 | 4.3 | 15(A) | 54-1/2 x 22 x 24 |
| AMP60S1A | 208/230 | 60 | 3/4 | 3 | 4.4 | 15(A) | 54-1/2 x 22 x 24 |

